Valley Acousticoat

Valley Acousticoat is a heavy bodied, water based flat latex paint formulated with ceramic microspheres and sound absorbing fillers.

The combination of a high loading of the Ceramic Microspheres with their vacuum centers reduces sound transmission and the soft pigment fillers absorb sound and prevent it from bouncing off the surface.

USES:
Valley Acousticoat is for use on interior surfaces including drywall ceilings and walls, plaster, primed metal and wood. This product is an inexpensive, easy to apply surface coating with superior sound absorbing properties as compared to conventional paints.

Valley Acousticoat is the ideal paint for interior ceilings as the heavy concentration of insulating ceramics and other pigments provides a highly reflective heat barrier to the painted surface reducing heat intrusion into the air conditioned spaces below.

The small texture helps in hiding surface defects such as drywall joints, dings and dents.

Surface Preparation:
Surfaces must be clean and free of dirt, mildew, grease, excess chalk, loose or scaling paint. Repair or replace any deteriorated surfaces. Scuff sand glossy surfaces.

Color	Bright White or tinted through Valley Tinting System
Finish	Flat
Solvent	Water
Dry Time/Recoat Interval	2 hours/8 hours
Flash Point	N/A
Coverage	4 m^2 /kg

Avoid prolonged or repeated contact with skin and breathing of vapors or spray mist. Coatings should only be applied when ventilation is adequate. If there is not adequate ventilation, applicators should wear respirator protection.