Valley ADFIX

- Description :

is a high strength, quick setting floor tile adhesive with excellent application properties. **Valley ADFIX** is suitable for interior and exterior floors for use on all types of dimensionally stable masonry substrates such as sands/cement screed, concrete, etc. It is both hydraulically and organically bound, guaranteeing excellent adhesion of the tile to the surface.

Valley ADFIX provides the following benefits: • Excellent adhesion • Improves durability • Quick setting • Easy workability • Water resistant

- Areas of application :

High strength ceramic, stone and mosaic tile adhesive for use on all type of masonry substrates such as sand/cement screed, precast concrete, gypsum board, where a fast setting time is required. Can be grouted after 3 hours so it is ideal for renovation work.

- MIXING :

Add about 7-7.5 litres of water to 25kg of **Valley ADFIX** and mix thoroughly to a thick and creamy consistency. Let it stand for 5 minutes, re-stir and apply.

-Technical Data :

Product	Cementitious high strength quick setting tile adhesive.
Binder	Hydraulic and organic binders
Color	White/Grey
Consumption	Trowel No. 4: 2.0-2.5 kg/m2 Trowel No. 5: 2.5-3.0 kg/m2 Trowel No. 6: 4.0-6.0 kg/m2
Pot Life	60 minutes
Mixing Water	28-30 %
Ready to Grout	3 hours
Ready for use	24 hours
Water Vapour Permeability tanking compound mix design)	100grs/m2 24hrs (2mm film)
Packaging	25 KG paper/pile bag
Storage	6 months in original unopened containers

HEALTH & SAFETY : Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material safety data sheet.