Valley Dry-Tex

Product Description:

- is a pre-mixed, colored, cement render, chemically-developed to be used as a finishing coat. Valley Dry-Tex 101 is fine, Valley Dry-Tex 102 is medium, and Valley Dry-Tex 103 is coarse. The material is supplied in ready-to-apply powder and consists of Portland cement, selected graded fillers, crushed stone of different sizes, high-quality polymers, and special additives to enhance the workability properties, adhesion, resistance to weather conditions. It only requires the addition of water prior to use in site on smooth concrete surfaces or plastering of brick walls.

Advantages:

- Resistant to different weather conditions because of the high-quality of all materials used in manufacturing.

- Easy of application and use after adding water to make homogeneous mixture which gives high productivity rates.

- It can be used manually by a trowel or a spraying machine. Finishing by choice.

- It gives attractive decorative appearance with different forms and multiple colors.

Technical Specifications:

PROPERTY	UNIT	Valley Dry-Tex 101	Valley Dry-Tex 201	Valley Dry-Tex 301
Color	-	24 colors according to the material's catalogue		
Dry Density	Kg / liter	1.6 ± 0.1		1.7 ± 0.1
Application Period	Minute	30 – 45 according to the temperature		
Compressive Strength	Kg / cm2	260 – 291	253 – 267	240 – 252
Water Absorption by Weight (28 Days)	%	0.17 – 0.529	0.431 – 1.093	0.354 – 1.09
Sulphate and Chloride Salts Resistance	-	Excellent resistance with no effect		
Coverage Rate	M2 / 25 kg	10	9	8

Method of Application:

- Surfaces should be cleaned from dust, oils and grease, and sprayed with water before application.

- Add 7 – 8 liters to each 25 kg bag of Valley Dry-Tex, and stir well for 5 minutes.

- Spread the material on the surface with a trowel or spraying machines in the required thickness.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Safety Precautions:

- Wear gloves, overall, and glasses during handling and application.

- In case of skin contact, wash exposed area with plenty of water. In case of eye contact, consult a physician.

- Storage: For 12 months from the date of production in closed packs in a dry store away from humidity.