# Valley Star 2000

Description : Valley Star 2000 is an attractive semi gloss elastomeric finish based on acrylic emulsion for interior and exterior surfaces. It is high quality facades paints especially designed to give long lasting durability

Technical Data :

| | |
|---|---|
| Viscosity | 48±3 ku |
| Solid Content | 56±3% |
| Density | 1.28±0.03gm/cm3 |
| Coverage | 10-12 $m^2$/kg (Dry film thickness40-45µ) |

Substrates and surface preparation : Valley Star 2000 is recommended for application over bricks, plaster, concrete or cement sheets. All new or already painted surfaces should be free from dust, grease and waxes.

Product Features :

- Alkali resistant
- Washable (up to 30000 cycles)
- Excellent non-yellowing properties
- Excellent hiding power
- High whiteness
- Dirt pick-up resistant
- Excellent leveling
- Chalking resistant
- UV resistant

Application :

1. Apply Valley Sealer 990 in one coat
2. Apply Valley Blue Putty in two cross layers
3. Apply Valley Sealer 990 in one coat again
4. Apply suitable type of emulsion paint (Valley Star 990 or Valley Star 1000) in one coat
5. Apply Valley Star 2000 in two coats after dilution with water (15 % dilution) to reach the application viscosity

Drying time at 25 °C & 60% R.H :

Initial drying time 1h

Recoating time 4h

Final drying time 6h

Tools : Spray gun, brush or roller

Color : White and colored according to Valley color guide

Expiry : Two years from production date if stored in original sealed container at normal temperature. Keep away from direct sun light.